THE CLAIMS

The claims of the application, as amended, are:

- 1. (Currently Amended) A megaphone having:
- a headset including a microphone assembly, said microphone assembly including a microphone, a curved member for attaching the microphone assembly to the head of a user, and a stalk connecting the microphone to the curved member and being capable of being bent to position the microphone adjacent to the user's mouth for hands-free operation;

a body pack provided with a belt for securing the body pack about the waist of the user, the body pack incorporating an output horn which is mounted to be forwardly-directed in use; and

a body pack incorporating

a belt for securing the body pack about the waist of the user, the belt including an elongate flexible panel having opposite ends;

an output horn which is mounted proximate the centre of the panel to be forwardly-directed in use,

a battery pack mounted on said panel, separately from said output horn, between the output horn and one of said ends, and

an electronic module mounted on said panel, separately from said output horn, between the output horn and the other of said ends, which is powered by the battery pack through electrical conductors incorporated in said panel, and provides an audio frequency amplifier having a low signal level input and a high signal level output arranged to supply audio frequency power to the output horn through further electrical conductors incorporated in said panel; and

- a flexible cable connecting the microphone assembly to the body pack.
 - 2. (Currently Amended) A megaphone which includes:
- a headset incorporating

a microphone assembly, said microphone assembly including a microphone for receiving voice signals from a user, a curved member for attaching the microphone assembly to the user, and a stalk connecting the microphone to the curved member and

being capable of being bent to position the microphone adja-

cent to the user's mouth for hands-free operation;

- a body pack incorporating

a belt for securing the body pack about the waist of the user, the belt including an elongate flexible panel having opposite ends,

an output horn which is mounted on the belt proximate the centre of the panel to be forwardly-directed in use, a battery pack mounted on said panel, separately from said output horn, between the output horn and one of said ends, an electronic module mounted on said panel, separately from said output horn, between the output horn and the other of said ends, which is powered by the battery pack through electrical conductors incorporated in said panel and provides an audio frequency amplifier having a low signal level input and a high signal level output arranged to supply audio frequency power to the output horn through further electrical conductors incorporated in said panel, and a high frequency audio tone generator connected to the low signal level input of the audio frequency amplifier, and

manually operable means for controlling the tone generator to output an audio tone of substantially constant frequency to the input at an amplitude which overrides any voice signals from the microphone; and - a flexible cable connecting the headset to the body pack to conduct audio signals from the microphone to the input of the audio frequency amplifier such that, when the manually operable means is not being operated to output an audio frequency tone to the input of the amplifier the amplifier acts to amplify voice signals from the microphone.

3. (Currently Amended) A megaphone which includes:

- a headset incorporating

a microphone assembly, said microphone assembly including a microphone for receiving voice signals from a user, a curved ear hook member which is pre-formed to locate about the ear of the user, and a stalk connecting the microphone to the curved member and being capable of being bent to position the microphone adjacent to the user's mouth for handsfree operation;

- a body pack incorporating

a belt for securing the body pack about the waist of the user, the belt including an elongate flexible panel having opposite ends, a pair of straps secured to opposite ends of said panel, and a pair of moulded snap-fit connector parts secured to the two straps; panel to be forwardly-directed in use,
a battery pack mounted on said panel, separately from said
output horn, between the output horn and one of said ends,
and
an electronic module mounted on said panel, separately from
said output horn, between the output horn and the other of
said ends, which is powered by the battery pack through electrical conductors incorporated in said panel, and provides an
audio frequency amplifier having a low signal level input and
a high signal level output arranged to supply audio frequency
power to the output horn through further electrical conductors
incorporated in said panel; and

an output horn which is mounted proximate the centre of the

- a flexible cable connecting the headset to the body pack to conduct audio signals from the microphone to the input of the audio frequency amplifier such that the amplifier acts to amplify voice signals from the microphone.